




Buglo

Acrobat

MATERIAL SPECIFICATION



Let's play





1 Tube slide made of stainless steel AISI 304. The metal sheet is 2 mm thick and the end section is finished with a band made of pipe 33,7 mm. The surface is polished.




2 Plates of the walls made of colourful triple layered 15 mm HDPE polyethylene, in the highest quality, totally damp-proof and resistant to UV.




3 Plates of the walls and platforms made of colourful 13 mm HPL (black plates made of 8 mm HPL), in the highest quality, totally damp-proof and resistant to UV.



4 Anti-slip anthracite 10 mm HPL platform plate with a very high resistance to weather conditions and attrition.



5 Anti-slip 18 mm HDPE plate. Very high resistance to weather conditions and attrition.



6 Solid construction made of black steel S235JR, cleaned in the sandblasting process. Protected against corrosion by galvanizing and powder coating with polyester paint QUALICOAT attested.



7 Solid construction made of stainless steel AISI 304 totally resistant to weather conditions.



8 Innovative system of connectors of stainless steel chains with posts. Smooth finishing protects from injuries. The cover is made of polyamide.



9 Post endings finished with soft EPDM rubber.



10 System of connectors and clamps made of strong aluminum alloy. Aluminum is secured by the process of electrophoresis and powder coating with polyester paint UV resistant and QUALICOAT attested.




11 Connecting elements like screws, nuts, washers made of stainless steel. Vandal-proof screw plugs made of injection molded polyamide.



12 Attested 6 mm stainless steel chains.



14 Polypropylene ropes pp-multisplit type with a steel core and a diameter of 16 mm.



15 Solid and esthetic rope connectors made of injection molded polyamide.



16 Rope endings pressed in a sleeve made of durable aluminum alloy.



17 Cross connection of ropes clamped in sleeves made of durable aluminum alloys. Used in elements requiring extremely high strength.




18 Ends of ropes clamped in sleeves made of durable aluminum alloys.



19 Rope ladder steps and rope knots made of injection molded polyamide.



20 The passage module made of polypropylene rope with a diameter of 16 mm with a steel core and AISI204 stainless steel. Rope connections clamped in sleeves made of durable aluminum alloys.



21 The passage module made of polypropylene rope with a diameter of 16 mm with a steel core, AISI204 stainless steel and HDPE plates. Rope connectors made of injection molded polyamide. Ends of ropes clamped in sleeves made of durable aluminum alloys.



22 The passage module is made of a 6mm stainless steel chain, 15 mm thick HDPE boards and an 18 mm thick HDPE non-slip HDPE board.



23 Pyramid tensioner allows for the periodic tensioning of the rope. Material: stainless steel.